



NEW LOW PROFILE DIODES



Features:

- MT: SOD-123H/Mini-SMA package that is 40% thinner. Maximum height: 0.04
- MH: SOD-123T/Mini-SMA package with Heat Sink at the bottom, increasing current rating by 50%. Maximum height: 0.067
- HM: Schottky Bridge Rectifiers with Low Vf chips. Maximum height: 0.118
- All Halogen-Free and Lead-free

Schottky Barrier Rectifiers 40-150 Volts

1.0 Amp

[CDBMT140-HF](#)

[CDBMT160-HF](#)

[CDBMT1150-HF](#)

2.0 Amp

[CDBMT240-HF](#)

[CDBMT240-HF](#)

[CDBMT240-HF](#)

3.0 Amp

[CDBMH360-HF](#)

[CDBMH340-HF](#)

[CDBMH3100-HF](#)

Recovery Rectifiers 1.0 Amps, 200-1000 Volts

Fast

[CFRMT103-HF](#)

[CFRMT106-HF](#)

[CFRMT108-HF](#)

Super Fast

[CSFMT104-HF](#)

[CSFMT104-HF](#)

[CSFMT104-HF](#)

Ultra Fast

[CURMT103-HF](#)

[CURMT104-HF](#)

[CURMT107-HF](#)

General Purpose

[CGRMT4001-HF](#)

[CGRMT4004-HF](#)

[CGRMT4007-HF](#)

Low VF Schottky Bridge Rectifiers 40-100 Volts

1.0 Amp

[CDBHM140L-HF](#)

[CDBHM160L-HF](#)

[CDBHM1100L-HF](#)

2.0 Amp

[CDBHM240L-HF](#)

[CDBHM260L-HF](#)

[CDBHM2100L-HF](#)

*Press blue button for hyperlink to datasheet.