



Meritec's Hercules Cable Plug Termination with the optional LSZH cable and its receptacle embedded in the mating rugged circular MIL-38999 shell provides both a durable and high bandwidth interconnect scheme suitable for many Military, Aerospace and ruggedized high bandwidth applications not previously accommodated by industry standard interconnects.

FEATURES | BENEFITS

- Rugged light-weight aluminum MIL-38999 Series III size 9, 17, 23 threaded coupling circular shells. (sizes 11, 13, 15 under development)
- Keying: "N" Standard, "A", "B", "C", "D" Special Ordered
- Optional connectors available for both cable assemblies & pigtail assemblies
- Cable types available: 4X High Bandwidth cable with LSZH or PVC jacket & FEP insulated 28 Awg Twin-ax w/ Halar Expando
- Available in 26, 28, 30 Awg cable
- Supports data rates in excess of 10Gbps and differential pair signaling with low-skew pairs & shielding for maximum EMI/RFI protection
- Meets or exceeds SAS, InfiniBand, USB 2.0 & 3.0, PCIe Express Gen2, Serial I/O, Ethernet, CX4, 10G Ethernet and SATA specifications
- Matched impedance design of 100 Ohm
- Mated cycles – 500 minimum
- Fully electrically tested
- Custom lengths built to order. Please consult Meritec

SPECIFICATIONS

ELECTRICAL:

(mated connector pair, less cable)

- Impedance: $100 \pm 10\Omega$ differential at 100psec rise-time
- Crosstalk (NEXT): $< -30\text{dB}$ up to 5Ghz from multiple aggressors
- Insertion Loss: $< 1\text{dB}$ up to 5Ghz
- Power per contact: 3amp @ 10°C temp rise
- Low Level contact resistance: $< 20\text{m}\Omega$, (EIA-364-23)
- Insulation resistance: $> 100\text{M}\Omega$ for 1 min @ 300VDC, (EIA-364-21)
- DWV: No defect for 1 min @ 300 VDC, (EIA-364-20)

MECHANICAL:


- Contact material: Copper Alloy
- Standard contact finish: 50 μ inch min Au over 50 μ inch min Ni
- Aluminum shell w/ plating options
- Durability: 500 cycles

ENVIRONMENTAL:

- -65°C to $+175^\circ\text{C}$
- IP67, mated or capped condition
- 500 hour salt spray

MERITEC | 1382 W. JACKSON ST. PAINESVILLE, OHIO 44077
PHONE: 888-MERITEC / (440) 354-3148 | FAX: (440) 354-0509 | WWW.MERITEC.COM






Hercules Ruggedized Interconnect System



PIN STYLE	*DIM "A"	*DIM "B"	DIM "C"
SOLDER TAIL	.97 [24.6]	.15 [3.8]	.10 [2.5]
SOLDER TAIL	.97 [24.6]	.15 [3.8]	.20 [5.1]
SOLDER TAIL	1.39 [35.3]	.57 [14.5]	.10 [2.5]
SOLDER TAIL	1.39 [35.3]	.57 [14.5]	.25 [6.4]
PRESS FIT	1.39 [35.3]	.57 [14.5]	.10 [2.5]

* DENOTES WALL MOUNT ASSEMBLY DIMENSIONS

*OPTIONS (P1, P4)

- A.  HERCULES™ MIL-38999 HERMAPHRODITIC
- D.  MINI-SAS
- B.  4X IB STRAIGHT THUMBSCREW
- E.  QSFP
- C.  SFP+
- F. OTHER (RJ-45, USB, IPASS (PCIE))

Shell Size	Number of Differential Pairs	Protocol(s)	Number of Contacts
9	2	USB, SATA	8
17	18+6 Spares	IB,SAS,SATA,Serial I/O,PCIe	66
23	44+4 Spares	IB,SAS,SATA,Serial I/O,PCIe	145

CONFIDENTIAL AND PROPRIETARY NOTICE

This document and the information contained in it are confidential property of Meritec. The document and information are provided to you for your review and evaluation and must not be furnished or disclosed to other without prior written consent by an authorized representative of Meritec.