



# Asymmetric Ultrasonic Sensor Specification

## Series FHDA12A

Model Number: FHDA12A08LFPM

Version 1.0

Address: 28 Genting Lane, #08-07 Platinum 28, Singapore 349585

Tel: +65-6493 5035

Fax: +65-6493 5037

Website: <http://www.flezon.com>

Email: [flezon@flezon.com](mailto:flezon@flezon.com)

# 1. ELECTRICAL SPECIFICATIONS



**Model No.:** FHDA12A08LFPM

**Description:** AUS 12D 8H 10V PIN ALUMINIUM RoHS

MODEL NO.	FHDA12A08LFPM	
CONSTRUCTION	WATERPROOF TYPE	
FUNCTION	TRANSMITTER & RECEIVER	
DIAMETER ( A ) $\pm 0.3$	mm	$\varnothing 12.0$
HEIGHT ( B ) $\pm 0.3$	mm	8.0
SOUND PRESSURE LEVEL ( 0dB = 0.0002 ubar )	Min. 95.0 dB ( 10.0 V rms Sine Wave / 30.0 cm )	
SENSITIVITY	Min. -82.0 dB ( v / ubar )	
CENTER FREQUENCY	Hz	40000 $\pm$ 1000 Hz
Directivity ( deg ) X – axis	115.0 $\pm$ 15.0	
Directivity ( deg ) Y – axis	60.0 $\pm$ 10.0	
CAPACITANCE AT 1KHz	pF	1800 $\pm$ 15 %
ALLOWABLE INPUT VOLTAGE	p-p	140V ( 40 KHz ) Pulse width 0.5 ms / Interval 20 ms
HOUSING MATERIAL	ALUMINUM	
OPERATING TEMPERATURE	$^{\circ}$ C	- 40.0 ~ + 80.0
WEIGHT	3.0 g	


## 2. PHYSICAL DIMENSION






All dimensions stated are in mm

Tolerance:  $\pm 0.5\text{mm}$


TOP VIEW




BOTTOM VIEW





Directivity



X-axis Directivity In Sound Pressure Level



Y-axis Directivity In Sound Pressure Level



SIDE VIEW

SIDE VIEW

FLEZON

## Revision History

Revision	Date	Description
1.0	2011.01	First Released

FLEZON CONFIDENTIAL