

Magnetic Transducer Specification

Series HWT

Model Number: HWT084A5ALFMP

Version 1.0

Address: 28 Genting Lane, #08-07 Platinum 28, Singapore 349585

Tel: +65-6493 5035 Fax: +65-6493 5037

Website: http://www.flezon.com

Email: flezon@flezon.com

ALL RIGHTS ARE STRICTLY RESERVED. ANY PORTION OF THIS PAPER SHALL NOT BE REPRODUCED, COPIED, OR TRANSLATED TO ANY OTHER FORMS WITHOUT PERMISSION FROM FLEXXON GLOBAL LIMITED.



1. ELECTRICAL SPECIFICATIONS

Model No.: <u>HWT084A5ALFMP</u>

Description: MT TRANSDUCER 5V SMD LCP 2350Hz SP RoHS

	MODEL NO.	HWT084A5ALFMP
	OPERATING VOLTAGE RANGE (V)	3.0 ~ 7.0
	RATED VOLTAGE (V)	5.0
+	MAX. RATED CURRENT (mA)	90.0
	COIL RESISTANCE (Ω)	32.0 ± 3.0
+	MIN. SOUND OUTPUT AT 10 cm (dBA)	85.0
	RESONANT FREQUENCY (Hz)	2350
	OPERATING TEMPERATURE (°C)	- 30 ~ + 70
	TERMINAL	SMD
	HOUSING MATERIAL	LCP
	WEIGHT (g)	0.6

⁺ Value applying rated voltage reasonant frequency,1/2 duty, square wave


^{*} Value applying reasonant frequency, 1/2 duty, square wave, measuring current 60uA



2. PHYSICAL DIMENSION

All dimensions stated are in mm

Tolerance: ± 0.2 mm





Revision History

Revision	Date	Description	
1.0	2005.08	First Released	