




SWITCH CIRCUIT

MATERIAL AND FINISH AS BELOW

WHEN CARD IS EJECTED WHEN CARD IS INSERTED

A	Housing	PBT UL94V-0, Color: Black	E	Epoxy Base	Epoxy Black
B	Contact	Brass C3604, Contact Area:10u" Gold Plating Over Nickel	F	Main Body	Aluminum alloy , Nickel Plating
C	Shell	Aluminum alloy , Nickel Plating	G	O-Ring	Silicone Black
D	Nut	Aluminum alloy , Nickel Plating	H	Gland Cage	POM White



SPECIFICATION:

1. ELECTRICAL

1.1 Current Rating: 5A per pin

1.2 Voltage Rating: 125V

1.3 Water Proof: IP X7

2. ENVIRONMENTAL

2.1 Operating temperature range: -40°C ~ +85°C

P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12
PIN ASSIGNMENT											
216A-08MF0		M12 A Code Plug for Cable, 8Pin Male For Field Installable, Contact: 10u" Gold Plating									
PRODUCT NO.				DESCRIPTION							

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANGLES	ANG.	±5°
LINEAR	0.	±0.3
	0.0	±0.25
	0.00	±0.20
SCALE	AS SHOWN	UNIT: mm
DRAWN	Willis	2013/12/24
CHECKED	Angel	2013/12/24
APPROVED	Ken	2013/12/24



www.attend.com.tw

DRAWN NAME: M12 A- Code Plug for Cable 8Pin Male For Field Installable

PRODUCT NO. 216A-08MF0

FILE NAME 216A-08MF0_B_2

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE
1	ECR1700027	2017/10/26			
	INITIAL RELEASE	2013/12/24			

SIZE	A4	REV.	1.0
------	----	------	-----