



(COMPONENT SIDE)
PCB LAYOUT

205E-S A N 0-R
1 2 3 4

- 1.Type
- S:SMD type
- 2.Contact Plating
- A:Gold Flash
- 3.Shell Plating
- N:Nickel plating
- 4.Rohs

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	NYLON PA9T G.F	BLACK		1
2	PIN TERM.	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	Gold Flash; NI:40~60 u"; TIN:120 u" (100% pure Tin of lead free plating)	4
3	SHELL	BRASS T:0.3	NICKEL PLATED	NI:80~120u"	1

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANGLES	ANG.	±5°
LINEAR	0.	±0.3
	0.0	±0.25
	0.00	±0.20
SCALE	AS SHOWN	UNIT: mm
DRAWN	Willis	2012/08/03
CHECKED	Angel	2012/08/03
APPROVED	Ken	2012/08/03



www.attend.com.tw

△	Revise:								
△	Revise:								
△	Revise:								

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME
1			4			A4	1.0	205E-SAN0-R_B_1