


CDBMH120-G Thru. CDBMH1150-G

Reverse Voltage: 20 to 150 Volts

Forward Current: 1.0 Amp

RoHS Device




Features

- Batch process design, excellent power dissipation offers better reverse leakage current and thermal resistance.
- Low profile surface mounted application in order to optimize board space.
- Low power loss, high efficiency.
- High current capability, low forward voltage drop.
- High surge capability.
- Guardring for overvoltage protection.
- Ultra high-speed switching.
- Silicon epitaxial planar chip, metal silicon junction.
- Heat Sink bottom.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

Mechanical data

- Case: Molded plastic.SOD-123T/ Mini SMA.
- Terminals: Plated terminals, solderable per MIL-STD-750, method 2026.
- Polarity: Indicated by cathode band.
- Mounting Position: Any
- Weight: 0.018 gram(approx.).



Maximum Ratings (at T_A=25 °C unless otherwise noted)

Parameter		Symbol	CDBMH 120-G	CDBMH 130-G	CDBMH 140-G	CDBMH 150-G	CDBMH 160-G	CDBMH 180-G	CDBMH 1100-G	CDBMH 1150-G	Unit
Max. Repetitive peak reverse voltage		V _{RRM}	20	30	40	50	60	80	100	150	V
Max. Continuous reverse voltage		V _R	20	30	40	50	60	80	100	150	V
Max. RMS voltage		V _{RMS}	14	21	28	35	42	56	70	105	V
Max. averaged forward current (see fig.1)		I _O	1.0								A
Maximum Instantaneous forward voltage at I _F =1.0A		V _F	0.50			0.70		0.85		0.92	V
Max. Forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		I _{FSM}	30								A
Max.Reverse current	V _R =V _{RRM} T _J =25°C	I _R	0.2								mA
	V _R =V _{RRM} T _J =100°C	I _R	10								
Typ. Thermal resistance (Junction to case)		R _{θJC}	45								°C/W
Typ. Diode Junction capacitance (Note 1)		C _J	120								pF
Operating temperature		T _J	-55 to +125			-55 to +150					°C
Storage temperature range		T _{STG}	-65 to +175								°C

Note : 1. F=1MHz and applied 4V DC reverse voltage

Rating and Characteristic Curves (CDBMH120-G Thru. CDBMH1150-G)

Fig.1- Typical Current Derating Curve




Fig.2 - Typical Forward Characteristics




Fig.3 - Maximum Non-repetitive Forward Surge Current




Fig.4 - Typical Junction Capacitance






Fig.5 - Typical Reverse Characteristics



Reel Taping Specification



Mini-SMA/SOD-123T	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	1.90 ± 0.10	3.90 ± 0.10	1.68 ± 0.10	1.50 ± 0.10	178 ± 2.00	62.0 MIN.	13.0 ± 0.50
	(inch)	0.075 ± 0.04	0.153 ± 0.04	0.066 ± 0.04	0.059 ± 0.004	7.008 ± 0.079	2.440 MIN.	0.512 ± 0.020

Mini-SMA/SOD-123T	SYMBOL	E	F	P	P_0	P_1	T	W	W_1
	(mm)	1.75 ± 0.10	3.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	0.23 ± 0.10	8.00 ± 0.30	11.40 ± 1.0
	(inch)	0.069 ± 0.004	0.138 ± 0.004	0.157 ± 0.004	0.157 ± 0.004	0.079 ± 0.004	0.009 ± 0.004	0.314 ± 0.012	0.449 ± 0.039

Pinning information

Pin	Simplified outline	Symbol
PIN 1 Cathode PIN 2 Anode		

Marking Code


Part Number	Marking Code
CDBMH120-G	12
CDBMH130-G	13
CDBMH140-G	14
CDBMH150-G	15
CDBMH160-G	16
CDBMH180-G	18
CDBMH1100-G	10
CDBMH1150-G	115



xx / xxx = Product type marking code

Suggested PAD Layout

SIZE	Mini-SMA/SOD-123T	
	(mm)	(inch)
A	1.00	0.040
B	1.00	0.040
C	1.70	0.067
D	0.50	0.020
E	1.50	0.060
F	1.10	0.044
G	0.90	0.035
H	0.85	0.033
I	0.60	0.024



Standard Package

Case Type	Qty per Reel	Reel Size
	(Pcs)	(inch)
Mini-SMA/SOD-123T	2500	7