


# Single Phase Glass Passivated Silicon Bridge Rectifier

 $V_{RRM} = 100\text{ V} - 400\text{ V}$ 
 $I_O = 30\text{ A}$ 

## Features

- Epoxy Resin material compliant with 94V-0 standards of UL Material Flammability Provisions
- Compliant with RoHS Provisions
- Single in-line DIP package, compact size
- Low forward voltage, high forward current
- High surge current capability
- Types from 100 V to 400 V  $V_{RRM}$
- Small size, high heat-conducting performance
- Thermal welding performance: 260 °C/10 s
- Weight: 7.25 g (0.25 Oz)
- Not ESD Sensitive

**GBJ Package**


## Maximum ratings at $T_A = 25\text{ °C}$ (ambient temperature), unless otherwise specified

Parameter	Symbol	Conditions	GBJ30B	GBJ30D	GBJ30G	Unit
Repetitive peak reverse voltage	$V_{RRM}$		100	200	400	V
DC blocking voltage	$V_{DC}$		100	200	400	
Operating temperature	$T_j$		-50 to 150	-50 to 150	-50 to 150	°C
Storage temperature	$T_{stg}$		-50 to 150	-50 to 150	-50 to 150	°C

## Electrical characteristics at $T_A = 25\text{ °C}$ , unless otherwise specified

Resistive load, single phase, half sine wave, 60 Hz.


For capacitive load derate current by 20%.

Parameter	Symbol	Conditions	GBJ30B	GBJ30D	GBJ30G	Unit
Maximum average forward rectified current	$I_O$	$T_C = 98\text{ °C}$	30 <sup>(1)</sup>	30 <sup>(1)</sup>	30 <sup>(1)</sup>	A
		$T_A = 25\text{ °C}$	5.2 <sup>(2)</sup>	5.2 <sup>(2)</sup>	5.2 <sup>(2)</sup>	
Maximum forward surge current	$I_{FSM}$	8.3 ms pulse width, single pulse sine-wave, rated load, $T_j = 25\text{ °C}$	420	420	420	A
Maximum forward voltage	$V_F$	$I_F = 15\text{ A}$	1.05	1.05	1.05	V
Max. reverse current leakage at rated DC blocking voltage	$I_R$	$T_A = 25\text{ °C}$	5	5	5	$\mu\text{A}$
		$T_A = 125\text{ °C}$	500	500	500	
Insulation strengthg (Lead wire to case)	$V_{dis}$	AC Voltage: 1 minute, current leakage < 1 mA	2.5	2.5	2.5	kV
Fusing feature	$I^2t$	$1\text{ ms} \leq t < 10\text{ ms}$ , $T_j = 25\text{ °C}$	350	350	350	$\text{A}^2\text{s}$
Thermal resistance	$R_{\theta JA}$	without heatsink	22 <sup>(2)</sup>	22 <sup>(2)</sup>	22 <sup>(2)</sup>	°C/W
	$R_{\theta JC}$	with stated size heatsink	1.0 <sup>(1)</sup>	1.0 <sup>(1)</sup>	1.0 <sup>(1)</sup>	
Mounting torque	TOR		1.0 ( 0.8 Nm is recommended )			Nm


**Remarks:** (1) Install on PCB with stated size heat sink. In order to reach excellent heat dissipation performance, please coat thermal conductive silica gel in moderation, use M3 screw to screw up. Recommended heatsink size: 15.2\*15.2\*12.8 cm.

(2) Install on PCB without heatsink.


**Fig.1: Current Derating Curve**




**Fig.2: Typical Reverse Characteristics**



**Fig.3: Max. Surge Current**



**Fig.4: Rated Forward Features**



**Package dimensions and terminal configuration**

Product is marked with part number and terminal configuration.

