

LINK-PP is worldwide leader in discrete magnetic transformers and integrated RJ45 connector modules are designed and manufactured .

Integrated RJ45 Connector

- Single Port
- SMT 1X1
- Single Port with USB
- PoE+ (IEEE 802.3at) ...
- 1XN
- 2XN
- Vertical
- Low-Profile
- 10GBASE-T
- RJ45 Without Magnetics

Discrete Magnetic Transformers

- Single Port
- Dual Port
- Quad Port
- Low-Profile PCMCIA
- PoE/PoE+ (IEEE..
- 10G BASE-T

Optical Transceivers

- SFP28
- QSFP+
- CFP
- CXP
- SFP
- SFF
- 1X9
- QSFP28
- SFP+
- XFP

Products

Products>>Integrated RJ45 Connector

LN1104BB

LINK-PP LN1104BB 100% Cross JXR0-0015NL / J0011D01BNL pulse

LINK-PP Part Number:	LN1104BB
Pulse Part Number:	JXR0-0015NL / J0011D01BNL
Speed:	10/100 Base-T
Number of Ports:	1X1
Application-Lan:	Ethernet(NoN PoE)
Latch:	Down
PIN Type:	THT Solder
Temperature:	- 40 TO + 85



Documents

E-mail

Detailed information

Single Port RJ45 Connector with 10/100 Base-T Integrated Magnetics,Green/Yellow LED,Tab Down,RoHS

LINK-PP Part Number	LN1104BB
Pulse Part Number	JXR0-0015NL / J0011D01BNL
Application-Lan	ETHERNET(NoN PoE)
AutomDX	YES
Bst Circuit	YES
Configuration RX	T,C
Configuration TX	T,C
Contact Mating Area Plating	GOLD 6u"/15u"/30u"
Cores per Port	4
Diodes	NO DIODES
LED Option	GREEN/YELLOW
Latch	TAB DOWN
Number of Ports	1X1
PCB	FR4
PCB Mount Angle	SIDE ENTRY
PCB Retaining Post	T POST
Package Height (Inches)	0.528
Package Height (mm)	13.40

Package Length (Inches)	0.839
Package Length (mm)	21.30
Package Width (Inches)	0.626
Package Width (mm)	15.90
Pin Type	THT SOLDER
RoHS Compliant	YES-RoHS-5 WITH LEAD IN SOLDER EXEMPTION
Search	YES
Shield EMI Tabs	WITHOUT
Speed	10/100 BASE-T
Temperature	- 40 TO + 85°
Turns Ratio RX	1CT:1CT
Turns Ratio TX	1CT:1CT

With low price but high-quality UL Certification LN1104BB, J0011D01BNL, JXR0-0015NL on your service, LINK-PP is one of the best LN1104BB manufacturers.

