



- Integrated RJ45 Connector**
- Single Port
 - SMT 1X1
 - Single Port with USB
 - PoE+ (IEEE 802.3at) ...
 - 1XN
 - 2XN
 - Vertical
 - Low-Profile
 - 10GBASE-T
 - RJ45 Without Magnetics

- Discrete Magnetic Transformers**
- Single Port
 - Dual Port
 - Quad Port
 - Low-Profile PCMCIA
 - PoE/PoE+ (IEEE..
 - 10G BASE-T

- Optical Transceivers**
- SFP28
 - QSFP+
 - CFP
 - CXP
 - SFP
 - SFF
 - 1X9
 - QSFP28
 - SFP+
 - XFP

Products

Products>>Integrated RJ45 Connector

LPJ17633AENL

LINK-PP LPJ17633AENL 100% Cross 0845-2G1T-H5 / 0845-2G1T-S4 / 0845-2G1T-H5-F Belfuse



LINK-PP Part Number:	LPJ17633AENL
Belfuse Part Number:	0845-2G1T-H5 / 0845-2G1T-S4 / 0845-2G1T-H5-F
Speed:	10/100 Base-T
Number of Ports:	2X1
Application-Lan:	Ethernet(NoN PoE)
Latch:	Up/Down
PIN Type:	THT Solder
Temperature:	-40 TO + 85

Documents

[Download Data sheet](#)

Detailed information

2X1 RJ45 Connector with 10/100 Base-T Integrated Magnetics,Green/Green LED,Tab Up/Tab Down,RoHS	
LINK-PP Part Number	LPJ17633AENL
Belfuse Part Number	0845-2G1T-H5 / 0845-2G1T-S4 / 0845-2G1T-H5-F
Application-Lan	ETHERNET(NoN PoE)
AutomDX	YES
Bst Circuit	YES
Configuration RX	T,C
Configuration TX	T,C
Contact Mating Area Plating	GOLD 6u"/15u"/30u"
Cores per Port	4
Diodes	NO DIODES
LED Option	GREEN/GREEN
Latch	TAB UP/TAB DOWN
Number of Ports	2X1
PCB	FR4
PCB Mount Angle	SIDE ENTRY
PCB Retaining Post	T POST
Package Height (Inches)	1.059
Package Height (mm)	26.90

Package Length (Inches)	1.331
Package Length (mm)	33.80
Package Width (Inches)	0.661
Package Width (mm)	16.80
Pin Type	THT SOLDER
RoHS Compliant	YES-RoHS-5 WITH LEAD IN SOLDER EXEMPTION
Search	YES
Shield EMI Tabs	WITH
Speed	10/100 BASE-T
Temperature	- 40 TO + 85°C
Turns Ratio RX	1CT:1CT
Turns Ratio TX	1CT:1CT

With low price but high-quality UL Certification LPJ17633AENL, 0845-2G1T-H5, 0845-2G1T-S4, 0845-2G1T-H5-F on your service, LINK-PP is one of the best LPJ17633AENL manufacturers.

