


Product Search Data Sheet

# XRCGB25M000F2P00R0



## Appearance & Shape





Note: This datasheet may be out of date

Manufacturing Co., Ltd.

The crystal unit that realized small package and highly accurate frequency.

Please download the latest datasheet of XRCGB25M000F2P00R0 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=XRCGB25M000F2P00R0

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy resonators.

#### Features

1. The series is available in the applications to be necessary for high accuracy resonator. Especially, it is the best for the communication clocks such as S-ATA and USB2.0.

2. The resonator is extremerly small size  $(2.0 \times 1.6 \times 0.7 \text{ (mm)})$ , and contribute to reduction in mounting area.

3. The series complies to RoHS directive, being lead-free (phase 3).

### Applications

Other Usage	Consumer
-------------	----------

## Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Plastic Tape	3000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

# XRCGB25M000F2P00R0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of XRCGB25M000F2P00R0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> http://www.murata.com/en/products/productdetail?partno=XRCGB25M000F2P00R0

# Specifications

Shape	SMD
Frequency	25.0000MHz
Frequency Tolerance	±20ppm max. (25±3°C)
Operating Temperature Range	-30℃ to 85℃
Frequency Shift by Temperature	±20ppm max.
Frequency Aging	±5ppm max./year
Wash	Not avairable
Load Capacitance	6pF
Equivalent Series Resistance(max.)	150Ω
Drive Level(max.)	300µW

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Attention






# XRCGB25M000F2P00R0

Note: This datasheet may be out of date. <u>Please download the latest datasheet of XRCGB25M000F2P00R0 from the official website of Murata</u> <u>Manufacturing Co., Ltd.</u> http://www.murata.com/en/products/productdetail?partno=XRCGB25M000F2P00R0





**Temperature Characteristics** 

3 of 3

Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.