

Search by Part Number

Search by Specifications

Search in the Lineups

Search by Competitor's Part Number

Home > Products > Capacitors > Ceramic Capacitors > Product details  

Chip Monolithic Ceramic Capacitors for Automotive

▶ Please be sure to read here, before using a product. ▶ Cautions about imitations

GCM32ER71C226KE19#

"#" indicates a package specification code.


In Production ?



< List of part numbers with package codes >

GCM32ER71C226KE19L、GCM32ER71C226KE19K

Shape



L size	3.2 ±0.3mm
W size	2.5 ±0.2mm
T size	2.5 ±0.2mm
External terminal width e	0.3mm min.
Distance between external terminals g	1.0mm min.
Size code in inch(mm)	1210 (3225M)

Specifications

Capacitance	22µF ±10%
Rated voltage	16Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

References

Packaging	Specifications	Minimum quantity
L	φ180mm Embossed taping	1000
K	φ330mm Embossed taping	4000


Mass (typ.)

1 piece	110mg
---------	-------

Stock Check (Where to buy) 


PDF Catalogs

Download a PDF file of this page 


How to read part numbers 

Series Information 

Specifications

Detailed specifications sheet 
 -Rated value
 -Specifications and Test methods
 -Package
 -Caution, Notice (Storage, Soldering and Mounting, ...etc.)

Product data

Reliability test data (Typical data) 

φ180mm Reel

168g

[Top of page](#)

[Investor Relations](#) | [About Murata](#) | [Careers](#) | [Contact Us](#) | [my Murata](#)

[Site Policy](#) | [Privacy](#) | [Site Help](#) | [Site Map](#) Copyright © Murata Manufacturing Co., Ltd. All Rights Reserved.