


Product Search Data Sheet

XRCGB27M120F3M10R0



Appearance & Shape





Note: This datasheet may be out of date

Manufacturing Co., Ltd.

The crystal unit that realized small package and highly accurate frequency.

Please download the latest datasheet of XRCGB27M120F3M10R0 from the official website of Murata

http://www.murata.com/en-global/products/productdetail?partno=XRCGB27M120F3M10R0

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy resonators.

Features

1. The series is available in the applications to be necessary for high accuracy resonator. Especially, it is the best for the communication clocks such as S-ATA and USB2.0.

2. The resonator is extremerly small size $(2.0 \times 1.6 \times 0.7 \text{ (mm)})$, and contribute to reduction in mounting area.

3. The series complies to RoHS directive, being lead-free (phase 3).

Applications

Other Usage	Consumer
-------------	----------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Plastic Tape	3000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





XRCGB27M120F3M10R0

Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB27M120F3M10R0 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-global/products/productdetail?partno=XRCGB27M120F3M10R0

Specifications

Туре	HCR2016
Frequency	27.1200MHz
Frequency Tolerance	±30ppm max. (25±3°C)
Operating Temperature Range	-30℃ to 85℃
Frequency Shift by Temperature	±40ppm max.
Frequency Aging	±5ppm max./year
Wash	Not available
Load Capacitance	10pF
Equivalent Series Resistance(max.)	80Ω
Drive Level(max.)	300µW
Shape	SMD

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering






XRCGB27M120F3M10R0

Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB27M120F3M10R0 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-global/products/productdetail?partno=XRCGB27M120F3M10R0





Temperature Characteristics

Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3