



Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ LFB212G45SG8A192 \ from \ the \ of ficial \ website \ of \ Murata \ Manufacturing} }$ Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=LFB212G45SG8A192

# LFB212G45SG8A192












#### Appearance & Shape







A: Directional Input Mark

All the technical data and information contained herein are subject to change without prior notice

(in mm)



Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Available in the 2400MHz to 2500MHz frequency range.



## **Packaging Information**

Packaging	Specifications	Minimum Order Quantity
-	180mm Embossed Tape	4000

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/02/09

Note: This datasheet may be out of date

Please download the latest datasheet of LFB212G45SG8A192 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFB212G45SG8A192

## LFB212G45SG8A192



Applications	WLAN BT
Nominal Center Frequency(fo)	2450.00MHz
Bandwidth(BW)	fo±50.00MHz
Insertion Loss in BW I)	2.6dB max. (at 25°C)
Insertion Loss in BW II)	2.8dB max. (-40 to +85°C)
Attenuation(Absolute Value) I)	40dB min. at 880.00 to 960.00MHz
Attenuation(Absolute Value) II)	38dB min. at 1710.00 to 1990.00MHz
Attenuation(Absolute Value) III)	16dB min. at 2110.00 to 2170.00MHz
Attenuation(Absolute Value) IV)	30dB min. at 4800.00 to 5000.00MHz
Ripple(max.)	1.8dB
VSWR(max.)	2.4
Characteristic Impedance(Nom.)	50Ω
Power Capacity	500mW
Operating Temperature Range	-40℃ to 85℃
L x W (size)	2.00x1.25mm
Thickness(max.)	1.05mm

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/02/09


Note: This datasheet may be out of date


Please download the latest datasheet of LFB212G45SG8A192 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFB212G45SG8A192

## LFB212G45SG8A192







Frequency Characteristics

Spurious Response

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

