


LQM21NN_10 Series 0805/2012 (inch/mm)



■ Dimensions



(in mm)

Dimension of t	Inductance: 0.1 to 2.2 μ H	0.85 \pm 0.2
	Inductance: 2.7 to 4.7 μ H	1.25 \pm 0.2

■ Packaging

Code	Packaging	Minimum Quantity
D	ø180mm Paper Taping	4000
L	ø180mm Embossed Taping	3000
J	ø330mm Paper Taping	10000
K	ø330mm Embossed Taping	10000
B	Packing in Bulk	1000

■ Rated Value (□: packaging code)

Part Number	Inductance	Inductance Test Frequency	Rated Current	Max. of DC Resistance	Q (min.)	Q Test Frequency	Self-Resonance Frequency (min.)
LQM21NNR10K10□	0.1 μ H \pm 10%	25MHz	250mA	0.26 Ω	20	25MHz	340MHz
LQM21NNR12K10□	0.12 μ H \pm 10%	25MHz	250mA	0.29 Ω	20	25MHz	310MHz
LQM21NNR15K10□	0.15 μ H \pm 10%	25MHz	250mA	0.32 Ω	20	25MHz	270MHz
LQM21NNR18K10□	0.18 μ H \pm 10%	25MHz	250mA	0.35 Ω	20	25MHz	250MHz
LQM21NNR22K10□	0.22 μ H \pm 10%	25MHz	250mA	0.38 Ω	20	25MHz	220MHz
LQM21NNR27K10□	0.27 μ H \pm 10%	25MHz	250mA	0.42 Ω	20	25MHz	200MHz
LQM21NNR33K10□	0.33 μ H \pm 10%	25MHz	250mA	0.48 Ω	20	25MHz	180MHz
LQM21NNR39K10□	0.39 μ H \pm 10%	25MHz	200mA	0.53 Ω	25	25MHz	165MHz
LQM21NNR47K10□	0.47 μ H \pm 10%	25MHz	200mA	0.57 Ω	25	25MHz	150MHz
LQM21NNR56K10□	0.56 μ H \pm 10%	25MHz	150mA	0.63 Ω	25	25MHz	140MHz
LQM21NNR68K10□	0.68 μ H \pm 10%	25MHz	150mA	0.72 Ω	25	25MHz	125MHz
LQM21NNR82K10□	0.82 μ H \pm 10%	25MHz	150mA	0.81 Ω	25	25MHz	115MHz
LQM21NN1R0K10□	1.0 μ H \pm 10%	10MHz	50mA	0.40 Ω	45	10MHz	107MHz
LQM21NN1R2K10□	1.2 μ H \pm 10%	10MHz	50mA	0.47 Ω	45	10MHz	97MHz
LQM21NN1R5K10□	1.5 μ H \pm 10%	10MHz	50mA	0.50 Ω	45	10MHz	87MHz
LQM21NN1R8K10□	1.8 μ H \pm 10%	10MHz	50mA	0.57 Ω	45	10MHz	80MHz
LQM21NN2R2K10□	2.2 μ H \pm 10%	10MHz	30mA	0.63 Ω	45	10MHz	71MHz
LQM21NN2R7K10□	2.7 μ H \pm 10%	10MHz	30mA	0.69 Ω	45	10MHz	66MHz
LQM21NN3R3K10□	3.3 μ H \pm 10%	10MHz	30mA	0.80 Ω	45	10MHz	59MHz
LQM21NN3R9K10□	3.9 μ H \pm 10%	10MHz	30mA	0.89 Ω	45	10MHz	53MHz
LQM21NN4R7K10□	4.7 μ H \pm 10%	10MHz	30mA	1.00 Ω	45	10MHz	47MHz

Class of Magnetic Shield: Magnetic shield of ferrite

Operating Temperature Range (Self-temperature rise is not included): -40~85°C

Continued on the following page.


● This data sheet is applied for CHIP INDUCTORS (CHIP COILS) used for General Electronics equipment for your design.

⚠ Note:


- This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

Continued from the preceding page.

■ Q-Frequency Characteristics (Typ.)



■ Inductance-Current Characteristics (Typ.)



■ ⚠ Caution/Notice

⚠ Caution (Rating)

Do not use products beyond the rated current as this may create excessive heat.

Notice

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

● This data sheet is applied for CHIP INDUCTORS (CHIP COILS) used for General Electronics equipment for your design.

⚠ Note:

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, its specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.