

Resonators > CERALOCK (MHz) > Series













How to check EU RoHS Compliance of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specification

Global Part Number	CSTLS_G
Previous Part Number	CSTS_MG
Oscillating Frequency	3.40 to 10.00MHz
Initial Tolerance	±0.5%
Temp. Stability	±0.2% [-0.4% to +0.2%:Built-in Capacitance 47pF type]
Operating Temperature Range	-20 to 80•
Wash	Not Available
Ultrasonic Wash	Not Available
Capacitor	Built in
Frequency Tolerance	Available in ±0.3%,±0.2%
Use	
Applications	For consumer electronics

Details

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features, Applications](#)
-  [Temperature Characteristics](#)
-  [Basic Oscillation Circuit](#)
-  [Notice \(Storage and Operating Conditions\)](#)
-  [Notice \(Rating\)](#)
-  [Notice \(Soldering and Mounting\)](#)
-  [Notice \(Handling\)](#)
-  [Packaging](#)
-  [Minimum Quantity \(Supplementation\)](#)

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	500
Ammo Pack	2000
320Reel	
Magazine	
Box	