


10W isolated DC-DC converter in SIP package
Ultra-wide input and regulated single output



CE Patent Protection RoHS

FEATURES

- Ultra-wide 4:1 input voltage range
- High efficiency up to 88%
- I/O isolation test voltage 1.5k VDC
- High power density
- Input under-voltage protection, output short circuit, over-current protection
- Operating ambient temperature range: -40°C to +85°C
- Industry standard pin-out
- EN62368 approved

URB_S-10WR3 series of isolated 10W DC-DC converter products have an ultra-wide 4:1 input voltage and feature efficiencies of up to 88%, input to output isolation is tested with 1500VDC and the converters safely operate in an ambient temperature of -40°C to +85°C, input under-voltage protection, over-current, short-circuit protection and they are widely used in applications such as medical care, industrial control, electric power, instruments and communication fields.

Selection Guide

Certification	Part No.	Input Voltage (VDC)		Output		Full Load Efficiency ^② (%) Min./Typ.	Max. Capacitive Load (µF)
		Nominal (Range)	Max. ^①	Voltage (VDC)	Current (mA) Max./Min.		
CE	URB2403S-10WR3	24 (9-36)	40	3.3	2400/0	83/85	2200
	URB2405S-10WR3			5	2000/0	86/88	2200
	URB2409S-10WR3			9	1111/0	86/88	680
	URB2412S-10WR3			12	833/0	86/88	470
	URB2415S-10WR3			15	667/0	86/88	330
	URB2424S-10WR3			24	417/0	86/88	220

Notes: ① Exceeding the maximum input voltage may cause permanent damage;
② Efficiency is measured at nominal input voltage and rated output load.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Current (full load / no-load)	3.3VDC output	--	389/25	398/45	mA
	5VDC output	--	474/25	485/45	
	Others	--	474/9	485/18	
Reflected Ripple Current		--	50	--	
Surge Voltage (1sec. max.)		-0.7	--	50	VDC
Start-up Voltage		--	--	9	
Under-voltage Protection		5.5	6.5	--	
Input Filter		Capacitance Filter			
Hot Plug		Unavailable			
Ctrl*	Module on	Ctrl pin open or pulled high (3.5-12VDC)			
	Module off	Ctrl pin pulled low to GND (0-1.2VDC)			
	Input current when off	--	6	10	mA

Note: * The Ctrl pin voltage is referenced to input GND.

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Voltage Accuracy ^①	5% -100% load	--	±1.5	±2	%
Linear Regulation	Input voltage variation from low to high at full load	--	±0.25	±0.5	
Load Regulation ^②	5% -100% load	--	±0.5	±1	

Transient Recovery Time			--	300	500	μs
Transient Response Deviation	25% load step change, nominal input voltage	3.3V, 5VDC output	--	±5	±8	%
		Others	--	±3	±5	
Temperature Coefficient	Full load		--	--	±0.03	%/°C
Ripple & Noise ^③	20MHz bandwidth, 5% -100% load	3.3V, 5VDC output	--	60	120	mV p-p
		Others	--	75	150	
Over-current Protection	Input voltage range		110	160	230	%Io
Short-circuit Protection		Continuous, self-recovery				
Note: ① Output voltage accuracy for 0%-5% load is ±3% max; ② Load regulation for 0% -100% load increases to ±3%; ③ Ripple&Noise for 0% - 5% load is ≤ 300mV. Ripple and noise are measured by Fig.2.						

General Specification

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Isolation	Input-output Electric Strength Test for 1 minute with a leakage current of 1mA max.	1500	--	--	VDC
Insulation Resistance	Input-output resistance at 500VDC	1000	--	--	MΩ
Isolation Capacitance	Input-output capacitance at 100KHz/0.1V	--	1000	--	pF
Operating Temperature	See Fig. 1	-40	--	+85	°C
Storage Humidity	Non-condensing	5	--	95	%RH
Storage Temperature		-55	--	+125	°C
Pin Soldering Resistance Temperature	Soldering spot is 1.5mm away from case for 10 seconds	--	--	+300	
Vibration		10-150Hz, 0.75mm, 5G, 90Min. along X, Y and Z			
Switching Frequency *	PWM mode	--	500	--	KHz
MTBF	MIL-HDBK-217F@25°C	1000	--	--	K hours
Note:*Switching frequency is measured at full load. The module reduces the switching frequency for light load (below 50%) efficiency improvement.					

Mechanical Specifications

Case Material	Black flame-retardant and heat-resistant plastic (UL94 V-0)
Dimensions	22.00 x 9.50 x 12.00 mm
Weight	5.5g (Typ.)
Cooling method	Free air convection(20LFM)

Electromagnetic compatibility (EMC)

Emissions	CE	CISPR32/EN55032	CLASS B (see Fig.4-② for recommended circuit)	
	RE	CISPR32/EN55032	CLASS B (see Fig.4-② for recommended circuit)	
Immunity	ESD	IEC/EN61000-4-2	Contact ±6KV	perf. Criteria B
	RS	IEC/EN61000-4-3	10V/m	perf. Criteria A
	EFT	IEC/EN61000-4-4	±2KV (see Fig.4-① for recommended circuit)	perf. Criteria B
	Surge	IEC/EN61000-4-5	line to line ±2KV (see Fig.4-① for recommended circuit)	perf. Criteria B
	CS	IEC/EN61000-4-6	3 Vr.m.s	perf. Criteria A

Typical Characteristic Curves








Fig. 1



Design Reference

1. Ripple & Noise

All the DC-DC converters of this series are tested before delivery using the recommended circuit shown in Fig. 2. Please keep the wire of probe to copper as short as possible.




Fig. 2

2. Typical application

Input and/or output ripple can be further reduced by appropriately increasing the input & output capacitor values C_{in} and C_{out} and/or by selecting capacitors with a low ESR (equivalent series resistance). Also make sure that the capacitance is not exceeding the max. capacitive load value of the product.




Fig. 3

$C_{in}(\mu F)$	$C_{out}(\mu F)$
47	22

3. EMC compliance circuit




Fig. 4

Notes: For EMC tests we use Part ① in Fig. 4 for immunity and part ② for emissions test, chose according to the demand.

Fig. 4 List of components



Model	$V_{in}:24V$
FUSE	Choose according to actual input current
$C0, C4$	330µF/50V
$C1, C2$	10µF/50V
$C3$	22µF/50V
LCM1	1.4-1.7mH (TN150P-RH12.7*12.7*7.9)
$CY1, CY2$	1nF/2000VDC

4. The products do not support parallel connection of their output

5. For additional information please refer to DC-DC converter application notes on www.mornsun-power.com

Dimensions and Recommended Layout

THIRD ANGLE PROJECTION 



Note : Grid 2.54*2.54mm

Pin-Out	
Pin	Function
1	GND
2	Vin
3	Ctrl
5	NC
6	+Vo
7	0V
8	NC

NC: Pin to be isolated from circuitry

Note:
 Unit: mm[inch]
 Pin section tolerances: ± 0.10 [± 0.004]
 General tolerances: ± 0.50 [± 0.020]

- Note:
- For additional information on Product Packaging please refer to www.mornsun-power.com. Packaging bag number: 58210004;
 - The maximum capacitive load offered were tested at input voltage range and full load;
 - Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^\circ\text{C}$, humidity<75%RH with nominal input voltage and rated output load;
 - All index testing methods in this datasheet are based on company corporate standards;
 - We can provide product customization service, please contact our technicians directly for specific information;
 - Products are related to laws and regulations: see "Features" and "EMC";
 - Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Huangpu District, Guangzhou, P. R. China
 Tel: 86-20-38601850 Fax: 86-20-38601272 E-mail: info@mornsun.cn www.mornsun-power.com