




[PAGE BACK](#) [CLOSE](#)

**Product Name** 3-terminal Filters  
**Series** ACF Series  
**Type** 451832 Type  
**Part Number** ACF451832-333-TD01

Product Lifecycle Stage PROD



#### Specification

Mounting Method Flag	Yes	
Processing	MULTI-LAYER	
Shape	Chip	
Circuit Type	T Type	
Number of Circuits	Nom	1
Size Code	4518	
Body Length(L)	Nom	4.5 m m
Body Breadth(W)	Nom	1.8 m m
Body Height(T)	Nom	3.2 m m
Rated Capacitance	Nom	33000 p F
Rated Voltage	Max	50 V
Rated Current	Max	300 m A
Insulation Resistance	Min	1000 M Ohm
DC Resistance	Max	0.15 Ohm
Attenuation	Min	25 dB
Frequency Range of Attenuation	Min	7 M Hz
	Max	60 M Hz
Polarity Marking	No	
Soldering Method	Reflow,Iron Soldering	
Category Temperature Range	Min	-25 Cel
	Max	85 Cel
Storage Temperature Range	Min	-40 Cel
	Max	85 Cel
Weight	Nom	0.13 g

#### ⚠ [ Caution ]

Specifications which provide more details for the proper and safe use of the described product are available upon request.

#### ⚠ [ Notice of Revision and Improve ]

All specifications are subject to change without notice.

#### Summary/Applications/Feature

Summary	The ACF Series are T-type EMC filters incorporating ferrite chip beads and multilayer ceramic chip capacitors.
Applications	EMC filters for signal line and interface
Feature	The ACF Series are T-type EMC filters incorporating ferrite chip beads and multilayer ceramic chip capacitors.

#### Packaging

Packing	Blister (Plastic)Taping [180mm Reel]
Minimum Package Qty	Nom 1000 Pcs
Minimum Order Qty	Nom 1000 Pcs

[Details](#)

[PAGE TOP](#)

Copyright(c) 1996-2008 All rights reserved.