WPSPG Spark Gap Protectors – MS Series

Part Numbering System

<u>WPSPG</u>	-	<u>20</u>	<u>M</u>	200
(1)		(2)	(3)	(4)

- (1) World Products Spark Gap Protector
- (2) DC Spark-over Voltage Tolerance: (Example: 20=20% tolerance)
- (3) Series Type MS= Medium Current Surface Mount Series
- (4) DC Spark-over Voltage: (Example: 200 = 200V)

FEATURES:

- 1. RoHS Compliant and Halogen Free
- 2. UL497B File #E135015 (see specific voltage values)
- 3. Fast Responding
- 4. Low Capacitance
- 5. Zero leakage current
- 6. Stable electrical characteristics over time
- 7. Can withstand repeated surges
- 8. Symmetrical

DIMENSION in mm.



ELECTRICAL CHARACTERISTICS

Part Number	DC Spark-Over Voltage	Minimum Insulation Resistance		Maximum Capacitance (1KHz-6Vտax)	Surge current capacity (8/20µs)
	Vs(V)	Test Voltage(V)	ΙR οнм(M Ω)	C(pf)	(A)
*WPSPG-XXMS140	140	50	100	0.8	1000
*WPSPG-XXMS200	200	100	100	0.8	1000
*WPSPG-XXMS220	220	100	100	0.8	1000
*WPSPG-XXMS300	300	100	100	0.8	1000
*WPSPG-XXMS400	400	250	100	0.8	1000
*WPSPG-XXMS500	500	250	100	0.8	1000
WPSPG-XXMS600	600	250	100	0.8	1000
WPSPG-XXMS700	700	250	100	0.8	1000
WPSPG-XXMS1000	1000	500	100	0.8	1000

Note: Vs±XX% (DC Spark-over Voltage Tolerance 30% and 20%),140V device is only available in 30% tolerance.

*UL 497B recognized (30% tolerance only).

WP SPG - SPARK GAP PROTECTORS



Rev. 1.7

WPSPG Spark Gap Protectors - MS Series

ltem	
L	5.0 ± 0.5
D	2.8 ± 0.5
d	2.6 ± 0.5
t	0.4 ± 0.1

WPSPG Spark Gap Protectors - MS Series

TEST METHODS AND RESULTS

ITEM	TEST METHOD	STANDARD	
DC Spark over Voltage(Vs)	Measure starting discharge voltage (Vs) by gradually increasing applied DC voltage. Test current is 0.5mA max. And the DC voltage ascends up within as follow condition.		
	Vs <1000V 100V/second Vs >1000V 500V/second	Maat appaified value	
Insulation Resistance(IR)	Measure the insulation resistance across the terminal at regular voltage. But the test voltage doesn't go beyond the DC spark-over voltage.		
Capacitance	Measure the electrostatic capacitance by applying a voltage of less than 6V (at 1KHZ) between terminals.		
Static Life	10KV with 1500pf condenser is discharged through 0Ω resistor. 200 times at an interval of 10sec.	Rate of change 30%. Characteristics of other items must meet the specified value.	
Surge Current Capacity	The following impulse current for specified current applied \pm 5 times at 60 seconds intervals. Thereafter, outer appearance shall be visually examined. Impulse current 1.2/50µs & 8/20µs, 1000A, electrically connected with a resistor (1~2 Ω).	No crack and no failures	
Cold Resistance	Measurement after -40°C/1000 HRS & normal temperature/2 HRS.		
Heat Resistance	Measurement after 125°C/1000 HRS & normal temperature/2 HRS.		
Humidity Resistance	Measurement after humidity 90~95%(45°C) /1000 HRS & normal temperature/2 HRS.	spec.	
Temperature Cycle	10 times repetition of cycle -40°C/30min normal, temp/2 min 125°C/30min, measurement after normal temp/2 HRS.		
Solder Ability	Apply flux and immerse in molten solder $230\pm$ 5°C for 3sec up to the end surface of the electrodes. Check for solder adhesion.	The end surface is evenly covered by solder.	
Solder Heat	Measurement after the end surface of the electrodes is dipped up to into 260± 5°C solder for 10sec.	Conformed to rated spec.	

WPSPG Spark Gap Protectors - MS Series





NOTE: 1500 pcs per reel.



WP SPG - SPARK GAP PROTECTORS

Taping Specifications

Item	Size (mm)	
Р	4.0±0.1	
P0	4.0±0.1	
W	12.0±0.2	
F	5.50±0.05	
E	1.5±0.1	
D	Φ 1.5±0.1	
К	3.0±0.1	
t	0.30±0.05	
A0	3.0±0.1	
B0	6.0±0.1	



	Item	Size (mm)
	D	178mm
	d	13mm
<u>L</u>	L	15mm

Item	Size (mm)
А	185
В	179
С	67